

BRIDGE COMMAND CONTROLLER



FEATURES

- Controls Up To (6) Bridge Command Displays
- Brightness Control Knob (Dim to Black)
- Intuitive Display Control Functions
- Red LED Backlit For Night Viewing
- 10-30V DC input
- IP-65 Waterproof Front



Rear Inputs

SPECIFICATIONS

Controller

LCD Display

Backlight

- N/A

Active Display Area

- N/A

Brightness

- N/A

Resolution

- N/A

Contrast Ratio

- N/A

Pixel Pitch (mm)

- N/A

Viewing Angle

- N/A

DisplayColor

- N/A

Response Time

- N/A

Inputs

- N/A

Mechanical

IP Rating

- Fascial waterproof to IP65 standards when console mounted.

Construction

- Rugged Aluminum Alloy Chassis

Mounting

- Panel mount

Dimension

- 186mm (W) x 100mm (H) x 40.5mm (D)
- 7.3in (W) x 4in (H) x 1.6in (D)

Net Weight

- 1.2 lbs. / .054 kgs

Power

Voltage

- Operates on 12V and 24V systems

Power Consumption

- 9W / .75A (12V)

Environmental

Operating Temperature

- -10°C~60°C (14°F~140°F)

Non-Operating Temperature

- -20°C~60°C (-4°F~158°F)

Certification

- Designed to meet FCC Class A and IEC 60 945 specifications