

PILOT-19

COMMERCIAL MONITOR



SPECIFICATIONS

LCD DISPLAY

Backlight

- 19" LED Backlight

Active Display Area

- 376.32 x 301.06mm
- 14.8 x 11.8in

Brightness

- 800 cd/m²

Resolution

- 1280 x 1024 (SXGA)

Contrast Ratio

- 1,000:1

Pixel Pitch (mm)

- 0.294(H) x 0.294(V)

Viewing Angle

- 160°(H), 160°(V)

Display Color

- 16.7M

Response Time

- 5ms

Inputs

- VGAx1, DVIx1

MECHANICAL

IP Rating

- None - Pilot House Use Only

Construction

- Painted Steel Chassis

Mounting

- Panel (Flush) mount, VESA mount

Dimension

- 421.9mm(W) x 375.5mm(H) x 57.7mm(D)
- 16.6in(W) x 14.8in(H) x 2.27in(D)

Net Weight

- 6.8kg / 15 lbs

POWER

Voltage

- Operates on 12V and 24V systems

Power Consumption

- 20W / 1.6A (12V)

CERTIFICATION

- Designed to meet FCC Class A specifications

ENVIRONMENTAL

Operating Temperature

- -10°C ~ 50°C (14°F ~ 122°F)

Non-Operating Temperature

- -20°C ~ 70°C (-4°F ~ 158°F)

